



Garver Manufacturing, Inc.
 P.O. Box 306
 Union City, Indiana 47390, U.S.A.

**PRODUCT
 DATA SHEET**

GERBER DELUXE G CENTRIFUGES

The Garver Gerber Deluxe G series are carefully designed for the Gerber test. They are cast aluminum construction with a brushed satin finish and a specially built motor that develops the proper G force to perform the Gerber tests. The Deluxe G series is equipped with heater, brake, thermometer, thermostat, visiscope, motor and heater switches, heater pilot light, and Gerber adapters. Heavy duty motor bearings, carefully hand polished computer machined shafts, and an efficient oiling system will give you years of trouble free service. The Deluxe series will hold glassware 9.0" max height by 1.0" max diameter. All parts within the Deluxe G and Deluxe series are interchangeable except; motor and visiscope disc.



Deluxe G Series Specifications

Model #	424G	436G	
Type	Gerber Centrifuge	Gerber Centrifuge	
Body Material	319 Cast Aluminum	319 Cast Aluminum	
Overall Diameter	23.0"	23.0"	
Overall Height	16.5"	16.5"	
Net Weight	67 lbs	73 lbs	
Shipping Weight	83 lbs	89 lbs	
Shipping Size	26" x 26" x 23"	26" x 26" x 23"	
Voltage	115	115	
Hertz	60	60	
Motor HP	0.1	0.1	
Amps	8.0	8.0	
RPM	1084	1084	
G-Force/RCF	350 ±50	350 ±50	
Rotor Diameter	21.0"	21.0"	
Heater	750 Watt	750 Watt	
Thermostat	Adjustable 26° - 100° C	Adjustable 26° - 100° C	
Glassware Max Size	9.0" x 1.0"	9.0" x 1.0"	
Glassware Capacity	24 Gerber Bottles	36 Gerber Bottles	
Brake	Manual	Manual	
Switches	1 Motor DPST 1 Heater DPST	1 Motor DPST 1 Heater DPST	
Pilot/Warning Light	1 for Heater	1 for Heater	
Speed Indicator	Visiscope	Visiscope	
Thermometer	Alcohol Base -10° - 100° C	Alcohol Base -10° - 100° C	
Available Options	D L GB	D L GB	

Option Codes: (D) Digital Read Out, (L) Lockable Lid, (GB) Will perform Gerber and Babcock tests

All centrifuges come equipped with rotor, trunnions, and cups.

Other voltages and frequencies available.

Custom centrifuges available for plastic and glassware, 15ml – 250ml, 4-36 bottle capacity, up to 800 X G. Call for quotes